

SoundSense dB Damp

Water based visco-elastic damping compound that reduces structure-borne vibration in a variety of materials. By imparting vibration damping and a shift in the dominant frequency, the resulting noise reduction provides a means of improving the noise transmission loss in many applications.

- Improves fatigue life of treated surfaces
- Tough, durable and paintable
- Easily applied with trowel, brush, or spray
- Meets FMVSS 302
- Neutral color
- Use on metal, plastic, glass, ceramic surfaces



Applications:

Typical uses include new construction and equipment requiring damping treatment plus superior flame spread and smoke density ratings, including bus, rail, and marine applications. Also used in fan and blower housings, duct work, bins, chutes, hoppers, machine guards, and stadium seating.

PRODUCT DATA:

Odor	odorless when dry
Flammability	per ASTM E-84 Flame spread: 0 Smoke Density: 0
Temperature	Maximum service temperature 325° F
Typical Coverage	10 - 15 sq. ft./gal. @ 1/8" thickness

ORDER INFORMATION:

Available in.....	Weight
5 gallon pails	62 lbs.
55 gallon drums	650 lbs.

PROPERTIES:

Color	Beige
Total solids	62%
Viscosity	Paste
Wet density (g/cm ³)	1.43
Dry density (g/cm ³)	1.73
Wet density (LB/US gal)	11.9
Wet density (LB/imp.gal)	14.3
Thermal conductivity (BTU in/hr ft ² °F)	2.1
Flash point	None
Hardness, shore D	58
Thickness, in	N/A
Thickness, mm	N/A
Standard sheet size, in.	N/A
Standard sheet size, cm	N/A
Surface weight, lb/ft ²	N/A
Surface weight kg/m ²	N/A
Resistance to fungus (ASTM G-21 rating)	O*