

BARRIER

NoiseOut-1

NoiseOut 1 (NO-1) is a low cost, high performance, non-reinforced mass loaded vinyl noise barrier that is a minimum recommendation for large scale applications with minimal noise requirements. This flexible barrier is used in gypsum wall constructions to reduce the transmission of airborne noise, such as conversational speech. When utilized within a floor assembly or above a ceiling, NO-1 is effective at decreasing the transmission of noise to vertically adjacent spaces.

Features:

- Increases Transmission Loss
- Improves performance of wall, ceiling, and floor assemblies
- Accepted for use in NYC: MEA 415-05M
- Lead-free and Asbestos-free
- Does not shrink, rot, or cause metal corrosion

Technical Properties:

Roll Size: 4.5' x 30'
 Thickness: 0.098" (<1/8")
 Temperature Range: 0 – 180°F
 Weight: 0.75 lb. /sq. ft.
 Resistance: Water – Excellent
 Petroleum – Excellent
 Alkalis – Good
 Flame – Meets MVSS 302

Accessories

- Big Stretch Acoustical Sealant

Additional Information Available:

- Architectural Specifications
- Acoustical Properties
- Typical installation guidelines and details



Applications:

- Residential
- Commercial
- Room-to-room Acoustic Separation