

## BARRIER

### NoiseOut-2

**NoiseOut 2 (NO-2)** is a high performance, non-reinforced mass loaded vinyl noise barrier that is recommended for use in many sound critical spaces. This flexible barrier is used in gypsum wall, floor, and ceiling constructions to substantially decrease the transmission of airborne noise sources. Whether the disturbance is loud speech, high levels of Multimedia audio, or mechanical equipment, **NO-2** is effective at reducing noise transmission to critically adjacent spaces.



#### Features:

- Increases Transmission Loss
- High density for maximum noise reduction performance
- Lead-free and Asbestos-free
- Does not shrink, rot, or cause metal corrosion

#### Applications:

- Residential
- Condominium
- Commercial
- Recording Studios
- Music rehearsal studios and practice rooms
- Mechanical rooms

#### Technical Properties:

Roll Size:	4.5' x 30'
Thickness:	0.156" (≈ 5/32")
Temperature Range:	0 – 180°F
Weight:	1.25 lb. /sq. ft.
Resistance:	Water – Excellent
	Petroleum – Excellent
	Alkalis – Good
	Flame – Meets MVSS 302

#### Accessories

- Big Stretch Acoustical Sealant

#### Additional Information Available:

- Architectural Specifications
- Acoustical Properties
- Typical installation guidelines and details