

## INSULATION

### NoiseOut-1 Bounce

**NoiseOut 1 Bounce (NO-1 Bounce)** is a rubber-based floor underlayment which provides superior footfall and impact noise reduction. Made from 92% post-consumer recycled rubber tires, **NO-1 Bounce** is designed for use with engineered hardwood or laminate flooring in either a floated or glue-down assembly. **NO-1 Bounce** performs exceptionally in lightweight wood constructions since its mass provides additional separation from airborne noise sources. **NO-1 Bounce** is extremely versatile for a wide range of projects and applications.



#### Features:

- Reduces footfall and impact noise
- Additional mass aids in reducing airborne noise transmission
- Environmentally friendly, 92% post-consumer recycled content
- Quick and convenient installation

#### Applications:

- Residential
- Condominium
- Commercial
- Multi-family dwellings
- Dance studios
- Gyms and exercise rooms

#### Technical Properties:

Description:	Recycled rubber tire granules bonded with a polymer bonding agent
Thickness:	3mm ( <b>NO-1 Bounce</b> )
Roll Size:	4' x 50'
Temperature Range:	Passed Consumer Products Safety Commission FF-1-70 Pill Test
Chemical Reaction:	DO NOT use Bounce series with any type of petroleum based products.
Mildew Resistant:	The Bounce series is a breathable material that allows for the evaporation of moisture when certain conditions are met: temperature and humidity must be maintained, and all spills must be cleaned up immediately.

#### Additional Information Available:

- Architectural Specifications
- Acoustical Properties
- Typical installation guidelines and detail