

FLOOR UNDERLAYMENT

Syncork

Syncork is an economical, impact sound reducing underlayment designed for setting ceramic tile and natural stone. **Syncork** provides high energy impact noise reduction in a dimensionally stable, crack suppression synthetic layer. The low weight and manageable size of the sheets enable a quick and convenient installation. When **Syncork** is utilized in combination with an airborne noise barrier such as mass loaded vinyl, substantial noise reduction from both airborne and impact noise can be achieved.



Features:

- Impact noise reduction and crack suppression in a single product
- “Light commercial” rating as per ASTM C627 (Robinson Test)
- Compatible with radiant heat flooring
- Resists mold, mildew, heat, and cold
- Does not shrink, rot, or retain moisture

Applications:

- Residential
- Condominium
- Commercial
- Kitchens
- Bathrooms
- Foyers and entry ways
- Home Theaters

Technical Properties:

Tile Size:	4' x 4'
Thickness:	0.1875" (≈ 3/16" or 5 mm)
R-Value	1.5
Qty per box:	25 sheets / box
Weight:	28 lbs / box

Accessories:

- Perimeter Isolation Strips
- Syncork Tile Adhesive
- DriTac 7600 Urethane or 3M 1099 Adhesive (for use with vinyl barrier)

Additional Information Available:

- Architectural Specifications
- Acoustical Properties
- Typical installation guidelines and details